



Toll Free: 866-822-7758 Fax: 610-430-3588

## GXL

Automotive Thin Wall Cross-linked Polyethylene (XLP) Wire SAE J-1128 (-40C to 125C)

Lubker Distribution P/N	Awg. Size	Conductor Stranding	Nominal Insulation	Nominal Diameter	Approx. Lbs./Mft.	Standard Drum 22", 30"	Standard Reel
GXL20	20	7/28 Bare	0.023	0.086	6	30M', 40M'	5M'
GXL18	18	19/.0092 Bare	0.023	0.094	8	25M', 35M'	5M'
GXL16	16	19/29 Bare	0.023	0.105	12	15M', 30M'	5M'
GXL14	14	19/27 Bare	0.023	0.119	16	10M', 20M'	5M'
GXL12	12	19/25 Bare	0.026	0.145	25	10M', 15M'	3M'
GXL10	10	19/23 Bare	0.031	0.181	39	5M', 10M'	2.5M'
GXL8	8	19/21 Bare	0.037	0.216	60	4M', 6M'	1.5

- Can be used in automotive applications where higher heat resistance and small diameter is required.
- Meets Ford ESB-M1L 85B and Chrysler MS-8900 specifications.
- We can stripe, print, respool or drum pack to your customized specifications.
- Buy standard put-ups or multiples of standard put-ups for quicker delivery.
- Stocked in various solid colors and the WCWC part number abbreviation:

Black-BLK	Dark green-GRN	Light green-LTGRN	Purple-PUR	White-WHT
Brown-BRN	Gray-GRY	Orange-ORN	Red-RED	Yellow-YEL
Dark blue-BLU	Light blue-LTBLU	Pink-PNK	Tan-TAN	